

Hybrid Inverter

SUN- 3 / 3.6 / 5 / 6 K-SG04LP1-EU



Colorful touch LCD, IP65 protection degree



DC couple and AC couple to retrofit existing solar system

16

Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel

140

Max. charging/discharging current of 140A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-3K -SG04LP1-24-EU	SUN-3K -SG04LP1-EU	SUN-3.6K -SG04LP1-EU	SUN-5K -SG04LP1-EU	SUN-6K -SG04LP1-EU
Battery Input Data					
Battery Type	Lead-acid or Li-Ion				
Battery Voltage Range (V)	20~30	40~60	40~60	40~60	40~60
Max. Charging Current (A)	140	70	90	120	135
Max. Discharging Current (A)	140	70	90	120	135
Number of battery input	Yes				
Charging Curve	3 Stages / Equalization				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
PV String Input Data					
Max. DC Input Power (W)	3900	3900	4680	6500	7800
Rated PV Input Voltage (V)	370 (125~500)				
Start-up Voltage (V)	125				
MPPT Voltage Range (V)	150-425				
Full Load DC Voltage Range (V)	300-425				
PV Input Current (A)	13	13+13			
Max. PV I _{SC} (A)	17	17+17			
No.of MPP Trackers	1	2			
No.of Strings per MPP Tracker	1				
AC Output Data					
Rated AC Output and UPS Power (W)	3000	3600	5000	6000	
Max. AC Output Power (W)	3300*1	3690*1	5500*1	6600*1	
Max. Output Apparent Power (VA)	3300*2	3690*2	5500*2	6600*2	
AC Output Rated Current (A)	13.6/13	16.4/15.7	22.7/21.7	27.3/26.1	
Max. AC Current (A)	15/14.3	18/17.2	25/23.9	30/28.7	
Max. Continuous AC Passthrough (A)	35				40
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor	0.8 leading to 0.8 lagging				
Output Frequency and Voltage	50/60Hz; L/N/PE 220/230Vac (single phase)				
Grid Type	Single Phase				
DC injection current (mA)	THD<3% (Linear load<1.5%)				
Efficiency					
Max. Efficiency	97.60%				
Euro Efficiency	96.50%				
MPPT Efficiency	99.90%				
Protection					
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection				
Output Over Voltage Protection	DC Type II/AC Type III				
Certifications and Standards					
Grid Regulation	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
General Data					
Operating Temperature Range (°C)	-40~60°C, >45°C derating				
Cooling	Natural cooling				
Noise (dB)	<30 dB				
Communication with BMS	RS485; CAN				
Weight (kg)	14	15.1			
Size (mm)	330W x 433H x238D				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	5 years				

1. For Belgium, Max. Output Power(W): SUN-3K-SG04LP1-24-EU is 3000; SUN-3K-SG04LP1-EU is 3000; SUN-3.6K-SG04LP1-EU is 3600; SUN-5K-SG04LP1-EU is 5000; SUN-6K-SG04LP1-EU is 6000.
2. For Belgium, Max. Output Apparent Power (VA): SUN-3K-SG04LP1-24-EU is 3000; SUN-3K-SG04LP1-EU is 3000; SUN-3.6K-SG04LP1-EU is 3600; SUN-5K-SG04LP1-EU is 5000; SUN-6K-SG04LP1-EU is 6000.